

Technical data:

Connections KVM	Graphic	4 / 8 x DVI-D
	Keyboard / Mouse	4 / 8 x USB-B
	Keyboard / Mouse external	2 x USB-A
	Microphone / Speaker	4 / 8 Combo-Audio
	Microphone / Speaker external	2 x 3,5mm Audio
	Power supply	1 x DC-12V
Connection cable (Standard)	1 x DVI / 1 x USB-A / 2 x Audio 3,5mm Combo cable	8 x KD-KAB-102-DVI (1.8m)
Switch	LCD settings	5 Pressure switch
	ON / OFF	1 Pressure switch
	OFF (LCD folded)	1 Semi-covert pressure switch
LED-Display panel	Operation	1 x green/red
	Number	1 x blue
	Capital letters	1 x blue
	Scroll	1 x blue
LED-Display KVM	Port selection	16 x green
Emulation	Keyboard/ Mouse	USB
	Display	Yes
Port selection	Push Button / Hotkey / OSD	
Graphic	17" LCD	1280 x 1024
	Colors	16,2 Mio.
	Frame Rate	H: 31,0 KHz. – 81,0 KHz. V: 56,0 KHz. – 76,0 KHz.
	Viewing angle	H: 140° / V: 130°
	Bandwith	140 Mhz.
	Brightness	300 cd/m ²
	Contrast	700 : 1
	Reaktion time	4 ms.
	Pixel pitch	0,264mm (H) x 0,264mm (V)
	Backlight	LED
Input values	100 V. – 240 V. AC, 48 Hz – 62 Hz	
Output values	DC 12V., 4,16A	
Power consumption	230 V / 16,8 Watts	
Certification	RoHS, RoHS2, CE	
Environment	Operating temperature	-10 - 50°C
	Storage temperature	-20 – 60°C
	Humidity	0 – 80% relative humidity (non condensing)
Physical properties	Casing	High performance steel
	Color	RAL 9005
	Weight	16.8 kg incl. angles
	Dimension (L x W x H) w/o handle	555 x 450 x 44,5mm (19" / 1U)
	Dimension (L x W x H) w. handle	567 x 450 x 44,5mm (19" / 1U)
Packaging	Weight	17.8 kg
	Dimension (L x W x H)	74 x 62 x 18 cm