

AW-1701HD

- 17,3" FULL HD LCD Monitor with LED Backlight
- DVI and VGA Input
- 3 front USB
- Depth 640 mm only



AW-1701HD is a 17,3" FULL HD /LCD-Monitor, Keyboard-Drawer with LED Backlight. The new equipment ensures brilliant HD images and Monitoring to unprecedented quality. AW-1701HD sets a new standard in picture quality inside the server room. A value keyboard with number block and touchpad, the integrated DVI and VGA Input and 3 Front USB connectors are completing the external design. The casing conforms the 1U Standard, is easily installed and mountable with the included mounting kit.

Properties

- 1U 17,3" LCD console, 640mm depth
- Stepless, adjustable angle from 0 to 105° over high quality unique torque hinges
- Easy one man assembly with the included installation angles.
- Adjustable depth from 640mm up to 1140mm tread depth
- Chromed metal handle
- Practical knurled screws
- Integrated DVI and VGA Input
- 3 Front USB-Connectors
- High graphic resolution, up to 1920 x 1080 with 60Hz DDC, DDC2 and DDC2B

Keyboard versions

Available in following versions: German (DE), US-English (US), UK-English (UK), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH) and swedish / finnish (SWE/FI)

Versions available on request: Turkish (TK) and Russian(RU)

Trackball version is possible, in combination with a [Cherry G84-4400](#) Trackball Keyboard.

Specifications

- DVI-Graphic Card ensures always a proper resolution, even if the background needs to be rebooted.
- Integrated 3 Port-front USB2.0 device-Hub for shared use of USB2.0 und USB1.1 terminal device (for another Mouse, Scanner, Printer, Cameras, USB-Storage medium, etc.) to all PCs
- Independent / Shared change of USB2.0 device, ON/OFF-switchable audible signal
- OSD Menu in the following languages adjustable: German, English, Spanish, Italian, French, Portuguese, Korean, Cyrillic, Japanese, trad. Chinese, mod. Chinese
- Supports all USB suitable operating systems: for example DOS, Windows Series / Server 2008 / Server 2013, Linux, MacOS, etc.
- Compatible with MAC G3/G4, MACmini and iMAC. It works with Mac OS X 10.4.10 (and other systems)

Technical data:

Connections	Graphic	1 x DVI-I 1 x VGA
	Keyboard / Mouse	2 X USB-Typ-A
	External (Hub)	3 x USB 2,0 (Type-A)
	Power supply	1 x C13 IEC socket
Connection cable (included)	Graphic	1 x DVI-D (1,8m) 1 x VGA (1,8m)
	Keyboard / Mouse / Hub	2 x USB A-A
Switch	LCD settings	4 Pressure switch
	ON / OFF	1 Pressure switch
	OFF (LCD folded)	1 Semi-covert pressure switch
LED-Display panel	Operation	1 x green
	Number	1 x green
	Capital letters	1 x green
	Scroll	1 x green
Emulation	Keyboard/ Mouse	Yes (HID with USB1.1
	Display	Yes(A.S.R.)
Graphic	17,3" LCD	1920 x 1080 (DVI Single Link)
	Colors	16,2 Mio.
	Frame Rate	H: 31,0 KHz. – 81,0 KHz. V: 56,0 KHz. – 76,0 KHz.
	Viewing angle	H: 140° / V: 130°
	Bandwith	140 Mhz.
	Brightness	300 cd/m ²
	Contrast	700 : 1
	Reaktion time	4 ms.
	Pixel pitch	0,264mm (H) x 0,264mm (V)
	Backlight	LED
Input values	100 V. – 240 V. AC, 48 Hz – 62 Hz	
Output values	DC 12V., 4,16A	
Power consumption	230 V / 18,8 Watt	
Certification	RoHS, RoHS2, CE	
Environment	Operating temperature	0 – 40°C
	Storage temperature	-20 – 60°C
	Humidity	0 – 80% relative humidity (non condensing)
Physical properties	Casing	High performance steel
	Color	RAL 9005
	Weight	12,9 kg incl. angles
	Dimension (L x W x H) without handle	64,00 x 43,6 x 4,4cm (19" / 1U)
	Dimension (L x W x H) with handle	67,80 x 43,6 x 4,4cm (19" / 1U)
Packaging	Weight	17,1 kg
	Dimension (L x W x H)	77,5 x 58 x 21 cm