

Technical data:

| | | |
|---|--------------------------------------|--|
| Connections | Graphic | 8 x DVI-I Socket (use only DVI-D cable) |
| | Keyboard / Mouse | 8 X USB-Typ-B |
| | External | 3 x USB 2,0 (switchable) |
| | Power supply | 1 x DC-12V |
| Connection cable (not included in the delivery) | USB / DVI-cable | KAB-102DVI (1,8m) |
| Switch | LCD settings | 4 Pressure switch |
| | ON / OFF | 1 Pressure switch |
| | OFF (LCD folded) | 1 Semi-covert pressure switch |
| LED-Display panel | Operation | 1 x green |
| | Number | 1 x green |
| | Capital letters | 1 x green |
| | Scroll | 1 x green |
| LED-Display KVM | Port/Switch | 8 x green (Port) |
| | | 8 x red (USB) |
| Emulation | Keyboard/ Mouse | Yes (HID with USB1.1 |
| | Display | Yes(A.S.R.) |
| Port selction | Hotkey /Key sequence of keyboard | |
| Graphic | 17,3" LCD | 1920 x 1080 (DVI Single Link) |
| | Colors | 16,2 Mio. |
| | Frame Rate | H: 31,0 KHz. – 81,0 KHz. V: 56,0 KHz. – 76,0 KHz. |
| | Viewing angle | H: 140° / V: 130° |
| | Bandwith | 140 Mhz. |
| | Brightness | 300 cd/m ² |
| | Contrast | 700 : 1 |
| | Reaktion time | 4 ms. |
| | Pixel pitch | 0,264mm (H) x 0,264mm (V) |
| | Backlight | LED |
| Input values | 100 V. – 240 V. AC, 48 Hz – 62 Hz | |
| Output values | DC 12V., 4,16A | |
| Power consumption | 230 V / 18,8 Watt | |
| Certification | RoHS, RoHS2, CE | |
| Environment | Operating temperature | 0 – 40°C |
| | Storage temperature | -20 – 60°C |
| | Humidity | 0 – 80% relative humidity (non condensing) |
| Physical properties | Casing | High performance steel |
| | Color | RAL 9005 |
| | Weight | 12,9 kg incl. angles |
| | Dimension (L x W x H) without handle | 64,00 x 48,2 x 4,4cm (19" / 1U) |
| | Dimension (L x W x H) with handle | 68,3 x 48,2 x 4,4cm (19" / 1U) |
| Packaging | Weight | 17,1 kg |
| | Dimension (L x W x H) | 77,5 x 58 x 21 cm |