

Technical data:

Connections	Graphic	8 x DVI-I Socket (use only DVI-D cable)
	Keyboard / Mouse	8 X USB-Typ-B
	External	3 x USB 2,0 (switchable)
	Power supply	1 x DC-12V
Connection cable (not included in the delivery)	USB / DVI-cable	KAB-102DVI (1,8m)
Switch	LCD settings	4 Pressure switch
	ON / OFF	1 Pressure switch
	OFF (LCD folded)	1 Semi-covert pressure switch
LED-Display panel	Operation	1 x green
	Number	1 x green
	Capital letters	1 x green
	Scroll	1 x green
LED-Display KVM	Port/Switch	8 x green (Port)
		8 x red (USB)
Emulation	Keyboard/ Mouse	Yes (HID with USB1.1
	Display	Yes(A.S.R.)
Port selction	Hotkey /Key sequence of keyboard	
Graphic	19" LCD	1280 x 1024 (DVI Single Link)
	Colors	16,2 Mio.
	Frame Rate	H: 31,0 KHz. – 81,0 KHz. V: 56,0 KHz. – 76,0 KHz.
	Viewing angle	H: 140° / V: 130°
	Bandwith	140 Mhz.
	Brightness	300 cd/m ²
	Contrast	700 : 1
	Reaktion time	4 ms.
	Pixel pitch	0,264mm (H) x 0,264mm (V)
	Backlight	LED
Input values	100 V. – 240 V. AC, 48 Hz – 62 Hz	
Output values	DC 12V., 4,16A	
Power consumption	230 V / 18,8 Watt	
Certification	RoHS, RoHS2, CE	
Environment	Operating temperature	0 – 40°C
	Storage temperature	-20 – 60°C
	Humidity	0 – 80% relative humidity (non condensing)
Physical properties	Casing	High performance steel
	Color	RAL 9005
	Weight	12,9 kg incl. angles
	Dimension (L x W x H) without handle	64,00 x 48,2 x 4,4cm (19" / 1U)
	Dimension (L x W x H) with handle	68,3 x 48,2 x 4,4cm (19" / 1U)
Packaging	Weight	17,1 kg
	Dimension (L x W x H)	77,5 x 58 x 21 cm